

Detailed Specification A130 - High Definition IP-STB

Size and weight	133mm x 180mm x 40mm. 480g (excluding accessories and packaging)	Operating environment	ETS 300-019-1-3 Class 3.1
Inputs	Ethernet 10/100 BaseT via RJ-45 shielded connector	EMC conformance	FCC Part 15 class B. 2004/108/EC EN55022
Outputs	HDMI 1.2a. with HDCP 10-way Mini-DIN for Composite video, Component (YPrPb), RGB, S-Video and analogue audio S/PDIF (optical). USB2.0 RF Loop through and Modulator	Safety approvals	CAN/ CSA-C22.2 No. 60065-03 EN60065
Power	5V DC at 1.5A via external power supply less than 8W typical usage (external supply input voltage 100-240V AC 50-60Hz, 0.8A max, output 5VDC 3A)	RoHS	2002-95-EC
Codecs	MPEG-2 MP@HL MPEG-4 pt10 AVC/H.264 HP@L4	WEEE	2002-96-EC
Video resolutions	Up to 720p and 1080i	Operating temperature	0°C (32°F) to 40°C (104°F)
Graphics resolutions	HD graphics up to 1280x720	Storage humidity	5% to 95% RH (non-condensing)
Audio	Analogue stereo audio out. Stereo and Dolby 5.1 surround via S-PDIF and HDMI. Dolby Digital pass through to external decoder	Accessories	
Security	Wide selection of DRM and Conditional Access support. HDCP on HDMI Macrovision on SD outputs (option)	Remote control	Standard
Memory	32MB Flash, 192MB RAM	Regional power supply with power cord	Standard
Front panel LEDs	Power on /IR command received (Red)	Anti-slip base	Standard
		IR keyboard	Standard
		HDMI cable	Optional
		SCART cable	Optional
		Component (YPrPb) cable	Standard
		S-VHS & Composite (CVBS) cable	Optional
		RGB cable	Optional

